

3-Axis Sanitary Elevator



The 3-Axis Sanitary Elevator is designed to assist in the pumping of low to medium viscosity fluids from drums and greatly reduce material handling time. It is portable and can reach four drums without rearranging the pallet.

FEATURES

- Adjustable for use with 120 to 400 lb open, semi-open and bung-type drums and 300 gallon totes
- Pump support rotates 180 degrees
- Mounting brackets for a variety of pumps
- Air control for raising and lowering functions
- Flow controls for raise and lower speed

OPTIONS

- Sanitary pumps installed
- Air regulator and shut-off controls for the pump

TYPICAL APPLICATIONS

- Air-powered operation for quickly raising and lowering inductors and/or pumps during drum/tote changeover.

TECHNICAL SPECIFICATIONS

Maximum air inlet pressure	125 psi (0.86 MPa, 8.6 bar)
Air inlet fitting.....	1/2" NPT F
Lowered height.....	80" (203 cm)
Lift travel.....	38" (97 cm)
Max. force @ 100 psi (7 bar)	80 lbs (36 kg)

ORDERING INFORMATION

Please contact EnDiSys for more information on ordering your 3-Axis Sanitary Elevator!



Home Office
14329 Northdale Blvd, Rogers, MN 55374
Voice: 763.428.5075 Fax: 763.428.5078

Illinois Office
120 Industrial Drive, Gilberts, IL 60136
Voice: 847.844.1854 Fax: 847.844.1857

Ohio Office
2962 Township Road 97, McComb, OH 45858
Voice: 763.286.4821 Fax: 763.428.5078

