

# Portable Pneumatic Elevator



The pneumatic elevator is designed to assist in the pumping of low to medium viscosity fluids from drums. When coupled to pumps and inductor plates, material-handling time is greatly reduced.

## FEATURES

- Adjustable for use with 120 to 400 lb open, semi-open and bung-type drums and 300 gallon open top totes
- Pump support rotates 40 degrees
- Connecting rod for mounting Graco and EnDiSys pumps
- Air regulator and shut-off controls for the pump
- Air control for raising and lowering functions
- Flow controls for raise and lower speed

## OPTIONS

- Sanitary inductors (various sizes)
- Non-Sanitary inductors (various sizes)
- Graco/EnDiSys sanitary pumps installed
- Low level alarms

## TYPICAL APPLICATIONS

- Air-powered operation for quickly raising and lowering inductors and/or pumps during drum/tote changeover.

## TECHNICAL SPECIFICATIONS

Maximum air inlet pressure .....	100 psi (0.7 MPa, 7 bar)
Air inlet fitting.....	1/2" NPT F
Lowered height.....	78" (140 cm)
Lift travel.....	44" (99 cm)
Max. force @ 100 psi (7 bar) .....	400 lb (181 kg)

## ORDERING INFORMATION

Please contact EnDiSys for more information on ordering your portable pneumatic elevator system!



Single Post Elevator



Dual Post Elevator



**Home Office** \_\_\_\_\_  
 14329 Northdale Blvd, Rogers, MN 55374  
 Voice: 763.428.5075 Fax: 763.428.5078

**Illinois Office** \_\_\_\_\_  
 120 Industrial Drive, Gilberts, IL 60136  
 Voice: 847.844.1854 Fax: 847.844.1857

**Ohio Office** \_\_\_\_\_  
 2962 Township Road 97, McComb, OH 45858  
 Voice: 763.286.4821 Fax: 763.428.5078

